

# Eaton Powerware 9390 160 kVA (22) Certified Refurbished UPS Units Available

[www.globalpwr.com](http://www.globalpwr.com)

## Eaton Powerware 9390 160 kVA UPS (RT) Certified Refurbished

Model: 9390-160/160

Available Voltages:

- 480V input/480V output
- 208V input/208V output
- 480V input/208V output bundled with IDC cabinet

Dimensions: 35.8" W x 31.6" D x 73.7" H

Weight: 960 Lbs

All units include the following features as standard equipment:

- Double Conversion Topology
- Unit efficiency up to 94%
- Unit output rating @ 0.9 Power Factor
- Input current distortion < 4.5%
- Full kW support from 0.9 lagging to 0.9 leading
- Supports Inductive loads to full kVA rating of system
- Advanced Battery Management™ (ABM) technology
- Scalable Architecture
- Variable DC bus for optimizing runtimes
- Castors with leveling feet
- Line and match design
- Multi language display
- Two internal X-slot card bays
- Patented HotSync® parallel firmware control
- Parallelable for Redundancy or Capacity

Available in 480-208 voltage when bundled with the IDC cabinet.

Integrated Distribution Cabinet with K13 transformer 480V-208V and (3) Breaker Bypass and (4) 225A Sub Feed Breakers.



### 9390 Battery Options:

IBC-L Battery Cabinet with the following runtime options:

- 5 minutes at full load 160 kVA / .8pf
- 8 minutes at full load 160 kVA / .8pf
- 11 minutes at full load 160 kVA / .8pf

Note: additional battery options available, please call for more details.

### Optional Accessories:

Maintenance Bypass Panel / Cabinet

Output Distribution Cabinets

Communication – SNMP, Modbus, Dry Contacts

FOR MORE INFORMATION:

**(800) 706-0906**  
[info@globalpwr.com](mailto:info@globalpwr.com)



©2021 Global Power Supply, Inc. All Rights Reserved  
Specifications are subject to change.