



Smart-UPS VT

10/15/20/30 kVA — Three-phase compact, high-performance power protection with scalable runtime

apc.com

Life Is On





Features and benefits

Smart-UPS™ VT offers centralized three-phase power protection with the reliability of the award-winning Smart-UPS family. Ideal for small data centers, large retail stores, regional offices, and dense power requirements, the Smart-UPS VT includes dual-mains input, automatic and maintenance bypasses, and scalable runtime with swappable batteries for increased availability. The rack-mounted version maximizes valuable floor space by incorporating UPS, power distribution, and additional battery capacity in a single rack. Low cost of ownership is achieved through best-in-class efficiency and a reduction in rating of electrical infrastructure — wires, transformers, and generators — due to the Smart-UPS VT Soft Start feature. The APC™ by Schneider Electric network management card with temperature monitoring provides remote monitoring and management through a simple Web/SNMP interface and allows integration with StruxureWare™. Serviceability is greatly enhanced by user-replaceable batteries, manageable extended run frames, and included start-up and standard on-site warranty services. All these features make the Smart-UPS VT the easiest UPS in its class to deploy, manage, and maintain.

Performance three-phase power protection in optimized footprint with scalable runtime for small data centers and other business-critical applications.

- Small footprint
- Scalable runtime
- Parallel capable
- Network manageability

Smart-UPS VT features

High availability

The Smart-UPS VT includes dual-mains inputs, automatic and maintenance bypasses, and scalable runtime with swappable batteries that are easy to replace for increased availability.

Its compatibility with the market-leading remote management applications, coupled with intuitive LCD user interface and LED status indicators, ensures the utmost availability for business-critical applications.

A versatile product

The Smart-UPS VT is available in a wide choice of configurations to best fit each specific installation need:

- 10/15/20/30 kVA
- Two different enclosures: Wide or narrow tower for optimized footprint
- Flexible runtime capacity:
 - Quick-swappable batteries and extended run enclosures
 - Up to four internal battery strings and external extended runtime enclosures
- Compatibility with generators, transformers, etc.

Reduced total cost of ownership (TCO)

The Smart-UPS VT intelligent design leads to a significant reduction of the TCO, making it the ideal choice over time:

- Best-in-class efficiency even at low load levels minimizes energy losses and operating costs
- Compact, small footprint for floor space optimization
- Input power factor correction reduces installation costs
- Reduction of electrical infrastructure rating requirements (wires, transformers, generators)



Smart-UPS VT features and options

High performance

- Up to 96% efficiency even at low load levels
- Large input voltage tolerance for compatibility with low-quality power grids
- Low input/output signal distortion
- Parallel capability up to four units for redundant configurations or capacity extension
- Rack-mounted configuration with isolation transformer

Comprehensive services offering

- On-site audits
- Maintenance contracts
- Battery replacement
- Remote monitoring for maximized uptime

Easy maintenance

- The product design allows quick maintenance leading to higher availability for the load
- Slide-in/out concept for the power module for a quick comeback to normal state
- Quick-swappable batteries for easy replacement

Manageability

The built-in features of the Smart-UPS VT, combined with APC leading management solutions, make it easy to manage and monitor. This significantly improves control over the energy supply and ensures high availability for the loads.

- Remote management of the UPS over network or telephone lines
- Centralized management via StruxureWare Central

Options

The Smart-UPS VT product offering provides a list of options:

- Floor-mounted maintenance bypass cabinet with or without distribution panel
- Floor-mounted parallel maintenance bypass cabinet for up to three UPS units
- Circuit breaker panel
- Extended runtime battery frames
- Bypass kits for UPS units and XR battery frames



Parallel operation bypass kit



Input transformer cabinet



Smart-UPS VT offers the ability to parallel up to four UPS units for redundancy.

StruxureWare for Data Centers software suite

Schneider Electric™ UPS units and secure power systems are a core component of any architecture designed for highly critical applications, such as data centers, industry environments, infrastructure, and buildings.

Intelligent energy management of these systems is enabled by Schneider Electric EcoStruxure™ integrated hardware and software system architecture. StruxureWare software applications and suites are a key element of the EcoStruxure architecture. StruxureWare software helps maximize system reliability and optimize operational efficiency.

StruxureWare for Data Centers software collects and manages real-time information about assets, resource use, and operation status throughout the data center life cycle. This data center infrastructure management software fully integrates the Galaxy™ PW. With full system visibility, managers can monitor and apply this information in order to optimize data center performance to meet IT-, business-, and service-oriented goals.



NOTE: Due to continued product enhancements, specifications are subject to change without notice. Data above is for reference only — not construction. Schneider Electric assumes no liability for damages as a result of any data errors or omissions in this document. Consult product guide specifications and installation drawings for further details.

A comprehensive portfolio of services

Schneider Electric Critical Power & Cooling Services provides the highest quality services and solutions by trained and trusted professionals. Our world-class services offer a smart way to build, operate, and maintain your critical applications, ensuring the right people, in the right place, at the right time.

Assembly and start-up service

Assembly and start-up service by a certified Field Service Engineer (FSE) ensures full factory warranty coverage. A Schneider Electric certified installation ensures your equipment is properly and safely configured for optimal performance. This service features a standard eight-hour, five-day response time, with upgrades available for off-business hours.

Advantage plans

Flexible service packages offer hassle-free system maintenance to improve uptime at a predictable cost. These packages provide your system with the care it needs to operate most efficiently while minimizing downtime. The Advantage Plus, Prime, Ultra, and Max are full-service packages that include technical support, preventive maintenance, quick on-site response, and remote monitoring. Response time upgrades are available.

Remote Monitoring Service (RMS)

RMS is an economical and easy-to-use Web-based service that lets you quickly respond to environmental or system changes. Trained technicians provide secure 24-hour monitoring of your physical infrastructure to diagnose and resolve problems before they become critical.

Preventive maintenance

Preventive maintenance on-site examinations of your critical systems are designed to prevent problems before they occur and keep your system running at maximum efficiency.

On-site warranty extension service

In the event of a system issue, an FSE will arrive on site by the next business day to isolate, diagnose, and correct the problem in as little time as possible, minimizing downtime. Upgrades to even faster response times are available.



Technical specifications

UPS rating kVA/KW (PF = 0.8)	10/8	15/12	20/16	30/24
AC power supply input				
Input voltage (V)	208 V (three-phase)			
Frequency (Hz)	40 – 70 Hz (auto-sensing)			
Power factor	< 0.98			
Input current total harmonic distortion	40 – 70 Hz with 10 Hz slew rate			
THDI	Less than 5% for full load			
Output				
Output voltage (V)	208 V			
Frequency (Hz)	57 – 63 Hz for 60 Hz nominal			
Power factor	0.8			
Overload	150% one minute, 125% 10 minutes			
Output voltage total harmonic distortion	Less than 5% for full load			
Performance				
Efficiency (at full load)	93.2%	93.0%	93.4%	93.1%
Operating temperature	0 °C to 40 °C (32 °F to 104 °F)			
Paralleling	Up to four units for either redundancy or capacity			
Dimensions (H x W x D) mm				
Wide tower (20/30 kVA)			1,500 x 523 x 854	
Narrow tower (10/15 kVA)	1,500 x 352 x 854		N/A	
Environmental conditions and noise				
Audible noise (dBA)	64 dB (57 dB at 70% load)			
Operating temperature	0 °C to 40 °C (32 °F to 104 °F)			
Operating relative humidity	0% to 95%			

Life Is On



Schneider Electric

132 Fairgrounds Road,
West Kingston,
RI 02892 USA
email: esupport@apc.com

www.schneider-electric.com

September 2016

©2016 Schneider Electric. All Rights Reserved.
Schneider Electric | Life Is On is a trademark and the property of Schneider Electric SE, its subsidiaries,
and affiliated companies. •998-1239850_GMA-US_B

This document has been
printed on recycled paper

