

# TRANSCUBE GLOBAL

**TRANS  
CUBE**

**GLOBAL SERIES**

The TransCube Global is a transportable, environmentally friendly double-walled fuel storage tank, that offers an efficient solution for onsite fueling and auxiliary supply.

With its fully transportable design and ability to fuel multiple pieces of equipment simultaneously, the TransCube will save you time and double or triple the run times of your equipment.

## MODEL: 20TCG



The TRANSCUBE™ 20TCG is a multi-task onsite fuel deployment solution for the direct supply to stationary diesel engines or the refueling of equipment on demand.

- ✦ **Transportable.** Full load lifting eyes, forklift pockets and internal baffles designed to allow handling of the tank full of fuel.
- ✦ **Stackable.** Easily stackable (2)-high full of fuel and (3)-high empty to reduce storage space requirements.
- ✦ **Accessible.** Access manway for maintenance and inspection of inner tank. Removable inner tank for servicing and cleaning.
- ✦ **Efficient.** Lockable equipment cabinet locks and secures equipment and fuel ports to run up to 3 pieces of diesel-powered equipment.
- ✦ **Environmentally Safe.** Double-walled, 110% containment eliminates the need for spill pans, UL 142 approved.

### SPECIFICATIONS

**STANDARD FITTINGS:** High accuracy contents gauge; 3" Fill Point; 1" pump feed with flexible dip pipe, strainer & non-return valve; (1) engine feed and return port set; pressure/vacuum vent; breather vent.

**OPTIONAL FITTINGS:** Complete transfer pump kits; water & particulate filter kits; fuel up to (2) feed & return blocks; fuel hose & quick couplers.

|   |  |
|---|--|
| <b>Capacity (Brim Fill) Litres:</b> 2091                                    | <b>Bund Material Thickness (mm/in):</b> 3mm/1/8"           |
| <b>Capacity (Brim Fill) US Gallons:</b> 552                                 | <b>Weight Empty (kg/lbs):</b> 823kg / 1814lbs              |
| <b>Capacity (Safe Fill) US Gallons:</b> 525                                 | <b>Weight Full (kg/lbs):</b> 2809kg / 6194lbs              |
| <b>Dimension Length (mm/in):</b> 2280mm / 90"                               | <b>Approvals:</b> UL142, CAN/ULC-S601-07, UN-IBC Type 31A, |
| <b>Dimension Width (mm/in):</b> 1150mm / 45"                                | US DOT, Transport Canada, NFPA30                           |
| <b>Dimension Height (mm/in):</b> 1320mm / 52"                               |  |
| <b>Dimension Cabinet Opening (mm/in):</b> 850.9 mm x 355.6 mm / 33.5" x 14" |  |