

TRANSTANK TTS SERIES



The TransTank TTS is an environmentally friendly, stationary bulk fuel container that offers an efficient solution for on site and large-scale projects that require on-demand fuel supply for generators and construction equipment.

The TransTank TTS is designed to exceed expectations on tank farms, long-term power systems and disaster relief applications.

MODEL: 200TTS



- ❖ **Equipment Cabinet.** Lockable equipment cabinet that secures all ports and fittings, as well as captures all spills and drips. Secure hose access enables fueling while cabinet is locked.
- ❖ **Connectivity.** Eight ports for feed and return.
- ❖ **Access Manway.** Easy access to inner tank for routine maintenance and cleaning.
- ❖ **Patented.** Patented double wall design.
- ❖ **Stackable.** Tanks can be stacked, reducing storage space requirements (while empty).
- ❖ **Double Walled, 110% Containment.** Built-in, weather proof bund.
- ❖ **Secure Hose Access.** Letterbox-style ports to enable continuous fueling while cabinet is locked.
- ❖ **Forklift Pockets.** Forklift pockets for easy movement when empty.

SPECIFICATIONS	
STANDARD FITTINGS: High accuracy contents gauge, 3" fill point, 1" pump feed, 3/4 inch feed and return set, Spare ports for additional feed /return assemblies, UL listed mechanical overfill prevention device, Battery operated bund alarm	
Capacity (Brim Fill) Litres: 26492	Weight Empty (kg/lbs): 7250kg / 15984lbs
Capacity (Brim Fill) US Gallons: 6998	Weight Full (kg/lbs): N/A (not transportable full)
Capacity (Safe Fill) US Gallons: 6649	Approvals: UL142, CAN/ULC-S601-14, AS1940, AS1692
Dimension Length (mm/in): 6058mm / 239"	CSC
Dimension Width (mm/in): 2438mm / 96"	
Dimension Height (mm/in): 2896mm / 114"	